

CF1 Honda

Forward Plate Compactor

The CF 1 offers premium operating comfort and optimum running characteristics for landscape/hardscape professionals or general construction.

The CF 1 is the smallest model vibratory forward plate compactor of the Weber MT product line. Replacing the existing model, the CF 1 Honda vibratory plate now boasts a significantly reduced weight thanks to Weber MT's talented design engineers.

The CF 1 is used for compacting in tight areas, for minor repair work and for paving work in the landscape/hardscape industry. Its removable guide bar makes it a cinch to transport the unit in the trunk of a car, while lifting handles make transport even easier. The unit can be ordered with additional accessories such as an integrated wheel kit and a poly pad for compacting pavers.

AREAS OF APPLICATION

landscape/hardscape compacting in tight areas
 compacting asphalt compacting pavers for maintenance
 minor repair work

ADVANTAGES OF CF1 HONDA:

- narrow base plate to reach tight places
- light weight for easy transport
- compact machine dimensions
- durable and rugged construction
- high working speed and good operating characteristics
- foldable, low-vibration guide bar
- closed v-belt guard
- quick and safe loading with lifting eye
- High-quality rubber grip on handle
- low hand-arm vibrations

AVAILABLE ACCESSORIES:

polyurethane pad
 wheel kit



Technical data

Type	CF1 Honda	
Operating weight CECE	lbs.	132
Operating width	in.	14
Centrifugal force	lbs.	2,248
Frequency	Hz	95
Engine manufacturer / type	Honda	GX 120 (gas)
Engine power output, max.	HP	3.6
Power output at operating speed	HP at r.p.m	2.5 at 3,000
Working speed	ft/min.	0-89
Dimensions (L x W x H), in.	in.	36 x 14 x 35

We reserve the right to alter specifications.

With quick disconnect water tank & throttle on guide bar.



CF2 Honda

Forward Plate Compactor

The CF 2 offers premium operating comfort and optimum running characteristics for landscape/hardscape professionals or general construction.

With compact dimensions, a folding guide bar and useful handles for lifting the CF2 is easy to transport anywhere. The special low-vibration guide bar (registered design), with user-friendly plastic coating, reduces hand/arm vibrations to ensure pure operational comfort for longer working hours. Now the CF2 also has an easy access throttle directly on the guide bar for extra ease of use.

Practical optional accessories such as: integrated wheel kit, 3.2 gallon easy disconnect water tank for asphalt compaction (flow of water can be adjusted by means of rotary knob) and polyurethane pad further facilitate work.

AREAS OF APPLICATION

landscape/hardscape

compacting asphalt or pavers for maintenance

Technical data

Type	CF2 Honda	
Operating weight CECE	lbs.	183
Operating width	in.	18
Centrifugal force	lbs.	3,372
Frequency	Hz	95
Engine manufacturer / type	Honda	GX 160 (gas)
Engine power output, max.	HP	4.9
Power output at operating speed	HP at r.p.m	3.7 at 3,000
Working speed	ft/min.	0-85
Dimensions (L x W x H), in.	in.	44 x 18 x 38

We reserve the right to alter specifications.

ADVANTAGES OF CF2 HONDA:

- compact machine dimensions
- durable and rugged construction
- high working speed and good operating characteristics
- foldable, low-vibration guide bar
- closed v-belt guard
- quick and safe loading with raised bar on frame
- low hand-arm vibrations
- throttle on guide bar
- water sprinkler system with 3.2 gallon tank (optional).

AVAILABLE ACCESSORIES:

- polyurethane pad
- wheel kit
- water sprinkler system (quick disconnect)





CF2 Honda

Forward Plate Compactor

The CF 2 offers premium operating comfort and optimum running characteristics for landscape/hardscape professionals or general construction.

With compact dimensions, a folding guide bar and useful handles for lifting, the CF2 is easy to transport anywhere. The special low-vibration guide bar (registered design), with user-friendly plastic coating, reduces hand/arm vibrations to ensure pure operational comfort for longer working hours.

Practical optional accessories such as: integrated wheel kit, 3.2 gallon water tank for asphalt compaction (flow of water can be adjusted by means of rotary knob) and polyurethane pad further facilitate work.

AREAS OF APPLICATION

landscape/hardscape

compacting asphalt or pavers for maintenance

Technical data

Type	CF2 Honda	
Operating weight CECE	lbs.	183
Operating width	in.	18
Centrifugal force	lbs.	3,372
Frequency	Hz	95
Engine manufacturer / type	Honda	GX 160 (gas)
Engine power output, max.	HP	4.9
Power output at operating speed	HP at r.p.m	3.7 at 3,000
Working speed	ft/min.	0-85
Dimensions (L x W x H), in.	in.	44 x 18 x 38

We reserve the right to alter specifications.

ADVANTAGES OF CF2 HONDA:

- compact machine dimensions
- durable and rugged construction
- high working speed and good operating characteristics
- foldable, low-vibration guide bar
- closed v-belt guard
- quick and safe loading with raised bar on frame
- low hand-arm vibrations
- throttle on guide bar
- water sprinkler system with 3.2 gallon tank (optional).

AVAILABLE ACCESSORIES:

- polyurethane pad
- wheel kit
- water sprinkler system





CF2A Honda

Forward Plate Compactor for Asphalt

As the number one machine for asphalt compaction, the CF2A is a must-have for any professional doing asphalt compaction.

The CF2A was developed in close cooperation with our customers. It rounds off the selection of forward plate models by adding a plate that is especially designed for asphalt compaction. Turning the machine into the quintessential asphalt compactor required a geometric modification of the base plate. The engineers also tweaked the grip of the guide bar until it offered the best possible handling for its professional users. The standard version of the asphalt plate includes a 3.2 gallon quick disconnect water tank with sprinkler system and an easily accessible throttle control.

AREAS OF APPLICATION

compacting asphalt landscape/hardscape
 compacting pavers for maintenance

Technical data

Type	CF2A Honda	
Operating weight CECE	lbs.	181
Operating width	in.	18
Centrifugal force	lbs.	3,372
Frequency	Hz	95
Engine manufacturer / type	Honda	GX 160 (gas)
Engine power output, max.	HP	4.9
Power output at operating speed	HP at r.p.m	2.5 at 3,000
Working speed	ft/min.	0-89
Dimensions (L x W x H), in.	in.	36 x 14 x 35

We reserve the right to alter specifications.

ADVANTAGES OF CF2A HONDA:

- BEST machine for asphalt compaction
- durable and rugged construction
- high working speed and good operating characteristics
- foldable, low-vibration guide bar
- closed v-belt guard
- quick & safe loading with raised bar in center of machine
- high-quality rubber grip on handle
- low hand-arm vibrations

AVAILABLE ACCESSORIES:

polyurethane pad
 wheel kit





CF3 Honda

Forward Plate Compactor

The CF 3 is for professionals and distinguishes itself by premium operating comfort, compact dimensions and optimum running characteristics.

With compact dimensions, a folding guide bar and useful handles for lifting, the CF3 is easy to transport anywhere. The special low-vibration guide bar (registered design), with user-friendly plastic coating, reduces hand/arm vibrations to ensure pure operational comfort for longer working hours.

Practical optional accessories such as: integrated wheel kit, 3 gallon water tank for asphalt compaction, and polyurethane pad further facilitate work.

AREAS OF APPLICATION

landscape/hardscape

compacting asphalt or pavers for maintenance

Technical data

Type	CF3 Honda	
Operating weight CECE	lbs.	212
Operating width	in.	20
Centrifugal force	lbs.	4,496
Frequency	Hz	95
Engine manufacturer / type	Honda	GX 160 (gas)
Engine power output, max.	HP	4.9
Power output at operating speed	HP at r.p.m	3.7 at 3,000
Working speed	ft/min.	0-85
Dimensions (L x W x H), in.	in.	46 x 20 x 38

We reserve the right to alter specifications.

ADVANTAGES OF CF3 HONDA:

- compact machine dimensions
- durable and rugged construction
- high working speed and good operating characteristics
- foldable, low-vibration guide bar
- closed v-belt guard
- quick and safe loading with raised bar on frame
- low hand-arm vibrations
- throttle on guide bar
- water sprinkler system with 3.2 gallon tank (optional).

AVAILABLE ACCESSORIES:

- polyurethane pad
- wheel kit
- water sprinkler system





CFR 90

Forward Plate Compactor

The CFR 90 is an alternative to the “standard” vibratory plates. The almost round base plate allows for high maneuverability in confined areas, and efficient compaction of sand, gravel and mixed soils.

As an export-oriented business and a specialist for walk-behind compacting equipment, Weber MT is uniquely equipped to accommodate special customer requests, including those from specific regions. In Scandinavia, for instance, customers frequently opt for vibratory plates that come with a base plate that is almost “round”.

The added agility of the machine especially benefits customers dealing with spatial constraints such as trenches or locations that require an alternative to a vibrating rammer. The round base plate allows the machine to turn and change direction and makes it easier to work in corners and tight spaces. Areas of application are hardscape/landscape, compacting along the edges of concrete block and around manholes and poles. This machine is equipped with a Honda GX 160 4-stroke gas engine and comes with a wheel kit for easy transport.

ADVANTAGES OF CFR 90:

- almost round base plate for better maneuverability
- integrated wheel kit for easy transport
- durable and rugged construction
- easily accessible throttle
- high working speed and good operating characteristics
- low hand-arm vibrations
- closed v-belt guard
- quick and safe loading with raised guide bar

Technical data

Type	CFR 90 Honda	
Operating weight CECE	lbs.	198
Operating width	in.	17
Centrifugal force	lbs.	3,147
Frequency	Hz	85
Engine manufacturer / type	Honda	GX 160 (gas)
Engine power output, max.	HP	4.9
Power output at operating speed	HP at r.p.m	3.7 at 3,000
Working speed	ft/min.	0-89
Dimensions (L x W x H), in.	in.	18 x 17 x 39

We reserve the right to alter specifications.

