


SILCAGRATE®



The SilcaGrate® is a structural support used to install any natural stone paver, concrete paver, or porcelain paver on elevated surfaces!


The SilcaGrate® is a sub-floor to support pavers on decks, docks, balconies, porches, rooftops, and other elevated surfaces. Made with recycled engineered polymers.



Dimensions: 16 x 18 x 1.5"

Weight: 4 lbs.

Certified To: INTERTEK – CCRR-0366



Span load rating:
16/100 (16" span and 100 psf live load)

Stair treads:
300 lb. load when supported on all 4 sides

Flame spread:
Less than 200 when tested in accordance
with ASTM E84

Pallet size:
186 grates, 40 x 48 x 52", 784 lbs.

Dead load of finished deck coverings
placed on the installed SilcaGrate panels
shall not exceed 30psf.

Certified for 2017 Florida Building Code
and 2019 California Building Code
per CCRR-0366

The SilcaGrate® measures 16"x18"x1.5"
(2 square feet) and weighs 4lbs. The grate
features easy installation with 4 deck screws
and allows random design patterns, provides
a safety net for the pavers, and eliminates
the maintenance of wood while expanding
your design options with a wide range of
finishes, colors, and textures.



StoneDeks System | (330) 831 -1585 | 14600 Commerce St. Alliance, OH 44601

sales@StoneDeks.com | www.StoneDeks.com |    