



OUTDOOR PORCELAIN 2021 COLLECTION



100%
MADE IN ITALY



OUTDOOR SPIRIT,
RESISTANCE AND VERSATILITY:
THESE ARE JUST A FEW OF THE FEATURES
OF 20 MM THICK PORCELAIN
STONEWARE.

PORCELAIN 2CM PAVER is ideal for public and private outdoor flooring and stands out for its exceptional technical performance.

A perfectly square and monocaliber porcelain stoneware slab with a 20 mm thickness that features surface finishes with high antislip performance (R11 A+B+C), with a wide range of special pieces that create visual continuity between indoor and outdoor spaces, making them perfect for swimming pools and wellness centres.



Rovere Impero & Rustic Grigio

BENEFITS



HIGH RESISTANCE TO BREAKING LOADS AND STRESS




HIGH NON-SLIP PERFORMANCE: R11 A+B+C



EASY TO CLEAN



HIGH RESISTANCE TO FROST AND FIRE



EASY TO INSTALL, REMOVE AND REPOSITION *



RESISTANCE TO THE WEATHERING ELEMENTS AND THERMAL SHOCK




RESISTANCE TO SALT AND INALTERABILITY OVER TIME



RESISTANT TO ACIDS




PERFECT CONTINUITY BETWEEN INDOOR AND OUTDOOR AREAS




REUSABLE

□ IT DOES NOT REQUIRE A SPECIALIZED TILE LAYER (IN CASE OF DRY INSTALLATION) NEITHER THE USE OF GLUES AND GROUTS (IN CASE OF DRY OR RAISED INSTALLATION)


INSTALLATION SOLUTIONS




DRY INSTALLATION ON GRAVEL




DRY INSTALLATION ON SAND





DRY INSTALLATION ON GRASS



TRADITIONAL INSTALLATION ON SCREEDS



RAISED INSTALLATION ON SUPPORTS



INTENDED USES

PORCELAIN 2CM PAVER'S MAIN FEATURES MAKE IT THE IDEAL SOLUTION FOR ANY TYPE OF PUBLIC AND PRIVATE

OUTDOOR FLOORING. PORCELAIN 2CM PAVER REPRESENTS THE BEST SOLUTION FOR:

- WALKWAYS IN GARDENS OR ON BEACHES
- TERRACES AND BALCONIES


- PATIOS, COURTYARDS, SWIMMING POOL EDGES, AND WELLNESS CENTRES
- DRIVE-OVER PATHWAYS



COLORS

20"X40"


WHITE



20"x40"




MOON



20"x40"




DESERT



20"x40"



DUST



20"x40"




DARK



20"x40"




SUNSET



20"x40"




ALPINE



20"x40"



SAND



20"x40"




SILVER



20"x40"




SMOKEY




20"x40"

EFESO



20"x40"

PERGAMO




20"x40"





SUNSET



SAND

COLORS

WOODTIME

CARPINO



16"x48"



8"x48"

ROVERE IMPERO



16"x48"



8"x48"

ROVERE SABBIA



16"x48"



8"x48"



SABBIA
16"x48"



**ROVERE
IMPERO**
16"x48"



CARPINO
8"x48"


COLORS

MODULAR PATTERN 4 SIZES

ASH RECTIFIED




18"x36"




18"x18"



24"x24"




12"x24"




Modular Pattern

SANDSTONE RECTIFIED



18"x36"



18"x18"



24"x24"




12"x24"



Modular Pattern



ASH



SANDSTONE

METAL RECTIFIED




18"x36"



18"x18"



24"x24"




12"x24"



Modular Pattern


COAL RECTIFIED



18"x36"



18"x18"




24"x24"



12"x24"



Modular Pattern



Modular Pattern 4 Sizes - 1 set include:

- ❶ 18"x36"x3/4" (2pcs) = 52.17%
- ❷ 24"x24"x3/4" (1pc) = 23.18%
- ❸ 18"x18"x3/4" (1pc) = 13.04%
- ❹ 12"x24"x3/4" (1pc) = 11.60%





METAL



COAL

COLORS

24"X24"

CARAMEL



24"x24"

DARK GREY




24"x24"

LIGHT GREY



24"x24"

FORGE



24"x24"

ASH




24"x24"

METAL




24"x24"

COAL



24"x24"

SANDSTONE



24"x24"

PIETRA GREY



24"x24"

RUSTIC GRIGIO



24"x24"

RUSTIC WHITE



24"x24"

SOFT CREAM



24"x24"

HONEY



24"x24"

MILK



24"x24"

POCONO



24"x24"

STORM



24"x24"



SOFT CREAM



RUSTIC GRIGIO

COLORS CEMENT LOOK 32"X32"

ANTRACITE



Rectified 32"x32"

AVORIO



Rectified 32"x32"

GRIGIO



Rectified 32"x32"



AVORIO 32"X32"




ANTRACITE



COLORS

MODULAR PATTERN 3 SIZES

DARK GREY



12"x24"



24"x24"




24"x36"



Modular Pattern

LIGHT GREY



12"x24"



24"x24"




24"x36"



Modular Pattern

Modular Pattern 3 Sizes - 1 set include :

- ❶ 24"x36"x3/4" (2pcs) = 66.67%
- ❷ 24"x24"x3/4" (1pc) = 22.22%
- ❸ 12"x24"x3/4" (1pc) = 11.11%



COLORS

MODULAR PATTERN 3 SIZES

CARMEL



12"x24"



24"x24"




24"x36"



Modular Pattern

HONEY




12"x24"



24"x24"




24"x36"



Modular Pattern

Modular Pattern 3 Sizes - 1 set include :

- ❶ 24"x36"x3/4" (2pcs) = 66.67%
- ❷ 24"x24"x3/4" (1pc) = 22.22%
- ❸ 12"x24"x3/4" (1pc) = 11.11%



COLORS

MODULAR PATTERN 3 SIZES

MILK



12"x24"



24"x24"



24"x36"



Modular Pattern

STORM



12"x24"



24"x24"




24"x36"



Modular Pattern


Modular Pattern 3 Sizes - 1 set include :

- ❶ 24"x36"x3/4" (2pcs) = 66.67%
- ❷ 24"x24"x3/4" (1pc) = 22.22%
- ❸ 12"x24"x3/4" (1pc) = 11.11%



MITERED EDGE COPINGS


DARK GREY



LIGHT GREY




LIGHT GREY
24"x36"



DARK GREY Mitered Copings

24"X48" & 24"X72"

DARK GREY



24"x48"



24"x72"

LIGHT GREY



24"x48"



24"x72"

SLATE



24"x48" Special Order - 4 weeks

HONEY



24"x48" Special Order - 4 weeks

TAUPE



24"x48" Special Order - 4 weeks

MILK



24"x48" Special Order - 4 weeks

CARAMEL



24"x48" Special Order - 4 weeks

STORM



24"x48" Special Order - 4 weeks





LIGHT GREY 24"x72"



DARK GREY 24"x72"

ANTIQUED - WAVE EDGE

16"X32" SPECIAL ORDER

BELGISCH GRANIT




WAVE EDGE 16"x32"

QUARZITE MIX



WAVE EDGE 16"x32"



QUARZITE MIX 16"x32"

DRIVEWAY-SIDEWALK

ORIENTE



9"x18"




9"x9"

QUARTIZE



9"x18"




9"x9"



QUARTZITE

48"X48" SPECIAL ORDER

VOLCANO GREY IN STOCK



48"x48"

ASPEN WHITE IN STOCK



48"x48"

ANTIQUE SAND



48"x48"

ANTIQUE EARTH



48"x48"

CORTEN



48"x48"

VOLCANO BLACK



48"x48"

ANTIQUE GREY



48"x48"



ASPEN WHITE



CORTEN

3CM PORCELAIN PAVERS

BLUESTONE DARK



16"x32" - **IN STOCK**,
24"x24"




BLUESTONE GREY



16"x32" - **IN STOCK**,
24"x24", 36"x36"



PIETRA BARGE




16"x32" - **IN STOCK**,
24"x24"

CEMENTO BLACK




16"x32", 24"x24"

CEMENTO TAUPE




16"x32", 24"x24"

CEMENTO SMOKE




16"x32", 24"x24"

SLATE BLACK




16"x32", 24"x24"

SLATE GREY




16"x32", 24"x24"

PIETRA BASALTO




16"x32", 24"x24", 36"x36"

PIETRA ANTRAZYT




16"x32"

PIETRA GREY




16"x32"

PIETRA OMBRA




16"x32", 24"x24"

PIETRA GRIGIONI




16"x32", 24"x24"

PIETRA MOKA




16"x32"

FORESTA CHIARO




16"x32"


FORESTA SCURO



16"x32"



BLUESTONE DARK



BLUESTONE GREY

PORCELAIN VENEER

AVORIO




8"x24"

BEIGE



8"x24"

BROWN



8"x24"

GRIGIO



8"x24"

CORNER




CLAY 3D PORCELAIN LEDGER

BEIGE



6"x8"x4"

TAUPE



6"x8"x4"

WHITE



6"x8"x4"



6"x24"



6"x24"



6"x24"

GREY



6"x8"x4"

DARK



6"x8"x4"

INSIDE CORNER



6"x8"x4"

SPECIAL ORDER



6"x24"



6"x24"



DARK



WHITE

ADJUSTABLE PAVER PEDESTALS


ADVANTAGES:

- EASY INSTALLATION
- EXCELLENT FOR HIDING AND EQUIPMENT
- ALWAYS A FLAT PAVING AND EASILY ACCESSIBLE
- EXCELLENT ABSORPTION OF STRUCTURAL MOVEMENT
- BETTER ACOUSTIC INSULATION
- HIGHLY RESISTANCE
- SIGNIFICANT LESS WEIGHT
- QUICK WATER DRAINAGE
- BETTER THERMAL INSULATION

IN-STOCK



	E3	E4	E5	E6	E6.5	E7
HEIGHT	1 1/8" - 1 5/8"	1 9/16" - 2 9/16"	2 3/8" - 4 1/8"	3 1/2" - 7"	7 1/2" - 11"	7" - 12 5/8"
COMPOSITION	1 base + 1 head (72 pcs/bx) 1 Spacer Tab (400 pcs/bx) 1 Shim (500 pcs/bx)	1 base + 1 head (54 pcs/bx) 1 Spacer Tab (400 pcs/bx) 1 Shim (500 pcs/bx)	1 base + 1 head (48 pcs/bx) 1 Spacer Tab (400 pcs/bx) 1 Shim (500 pcs/bx)	1 base + 1 head (40 pcs/bx) 1 Spacer Tab (400 pcs/bx) 1 Shim (500 pcs/bx)	1 base (48 pcs/bx) 1 head (36 pcs/bx) 1 Spacer Tab (400 pcs/bx) 1 Shim (500 pcs/bx)	1 base (48 pcs/bx) 1 extender (60 pcs/bx) 1 head (72 pcs/bx) 1 Spacer Tab (400 pcs/bx) 1 Shim (500 pcs/bx)



PEDCORRECTOR -
Base slope corrector
(0%-5% slope adjustable)

ADJUSTABLE PAVER PEDESTALS



BEFORE



AFTER

ADJUSTABLE HEIGHT:

We have a solution height from 1/8" to 50".

MATERIAL:

Polypropylene(PP), material thickness 4.5mm-6mm;
Composition 90% PP, 10% talc, UV and black masterbatch
100% recyclable

DIMENSIONS:

Head=diameter 5 7/8" - surface area 27.28 sq.inch
Base=diameter 7 7/8" - ground surface 48.83 sq.inch
Extender-extender diameter 4 3/4" - adjustable height

PERFORMANCE:

Resisting UV rays, weather, sea salt and almost all chemicals.
Temperature range: -40°F to +248°F (-40°C to +120°C).

APPLICATION:

Support for outdoor terraces with any kind of material: timber decking, stone, ceramic, composite material, metal, fiberglass grid ... Can be placed on any stable substrate, also over insulation panels.

SLOPE CORRECTOR FROM 0%-5% :


Slope correctors could compensate ground fall 0%-5%, making ideal levelling surface. It is assembled on the bottom of pedestals. Clients could choose to use it or not with different installing condition.

FIX COLLAR: Fix and lock height after adjustment, increase stability

SHIM: Anti-slip, reduce impact, absorb shock, compensate floor thickness difference.




BLUESTONE GREY



Scan for pedestal installation process video


RISE-IT



Rise-it 1/2"




Rise-it Shim 1/16"



Rise-it 1/8"



Rise-it Flat Top






Risers can be stacked 3 pcs high with an elevation of 1/2" increments. Up to 4 shims can be used in conjunction in 1/16" increments for optimal levelling.

APPLICATIONS:

- ROOFTOPS
- TERRACES & DECKS
- PATIOS
- BALCONIES, VERANDAS & PORCHES
- AROUND SWIMMING POOLS
- BETTER THERMAL INSULATION




RISE-IT





DRY INSTALLATION ON GRAVEL



THIS TYPE OF INSTALLATION IS RECOMMENDED FOR WALKABLE FLOORS.

PORCELAIN 2CM PAVER IS INSTALLED ON THE SUBSTRATE WITHOUT USING ADHESIVES OR FILLERS, THEREBY

CREATING WALKWAYS THAT CAN BE WALKED ON IMMEDIATELY. INTEGRATED AND ENVIRONMENTALLY-FRIENDLY.

INSTALLATION ON GRAVEL HAS THE ADVANTAGE OF ALLOWING THE DRAINAGE OF RAINWATER.


INSTALLATION INSTRUCTIONS

- ∞ LEVEL THE GRAVEL
- ∞ POSITION THE TILE
- ∞ USE CROSS SPACERS





DRY INSTALLATION ON SAND



INSTALLATION ON SAND IS PARTICULARLY SUITABLE FOR BEACHES AND LIDOS (ESPECIALLY IN LIGHT COLOURS).



INSTALLATION INSTRUCTIONS

∞ LEVEL THE SAND

∞ POSITION THE TILE

∞ USE CROSS SPACERS





DRY INSTALLATION ON GRASS

INSTALLATION INSTRUCTIONS

- ∞ LAY THE TILES BY SPACING THEM DEPENDING ON THE DESIRED AESTHETIC EFFECT AND REMOVE THE GRASSY SURFACE
- ∞ SPILL THE GRAVEL AND SAND STABILISER TO IMPROVE THE TIGHTNESS OF THE SUBSTRATE
- ∞ POSITION THE TILE







TRADITIONAL INSTALLATION ON SCREEDS *



THE EXTRAORDINARY
RESISTANCE OF THIS 30
MM FINE PORCELAIN


STONEWARE MEANS
PORCELAIN 2CM
PAVER, LAID WITH

THE TRADITIONAL
TECHNIQUE ON
SCREEDS, IS THE IDEAL

SOLUTION ALSO FOR
PAVING DRIVEWAYS.

INSTALLATION INSTRUCTIONS

- ∞ SPREAD THE ADHESIVE EVENLY USING THE DOUBLE COATING TECHNIQUE (BOTH ON THE SUBSTRATE AND ON THE BACK OF THE TILE)
- ∞ POSITION THE TILE
- ∞ USE CROSS SPACERS (5 MM JOINTS)
- ∞ GROUT THE FLOOR
- ∞ CLEAN THE SURFACE THOROUGHLY




PLEASE CHECK THE SUPPORT CAPACITY AND QUALITY OF THE LAYING SURFACE BEFORE INSTALLING THE TILES. LASTLY, A MINIMUM SLOPE IS ADVISED OF 1.5%.

THIS TYPE OF INSTALLATION REQUIRES OPTIMAL COPLANARITY OF THE SCREED, DOUBLE LAYER OF ADHESIVE, AND 5 MM JOINTS BETWEEN THE SLABS.





RAISED INSTALLATION ON SUPPORT



PORCELAIN 2CM PAVER IS THE PERFECT SOLUTION FOR OUTDOOR FLOATING INSTALLATIONS OVER 3 DIFFERENT TYPES OF POLYPROPYLENE LOAD BEARING SUBSTRATES.

THESE TILES ARE QUICK AND EASY TO INSTALL AND REMOVE AND CAN BE WALKED ON IMMEDIATELY.

INSTALLATION INSTRUCTIONS

∞ YOU ARE ADVISED TO CHECK THE SUPPORT CAPACITY AND QUALITY OF THE LAYING SURFACE BEFORE INSTALLING THE TILES. A MINIMUM SLOPE IS ADVISED OF 1.5%

∞ LAY THE TILES ON THE SUPPORTS PREVIOUSLY ARRANGED

∞ CHECK THE COPLANARITY AND LEVELLING OF THE SURFACE

∞ USE THE ADJUSTMENT KEY IF NECESSARY





LIGHT GREY 24"X48"
& MITERED EDGE COPINGS
IN STOCK



CUSTOM COPINGS & DRAINS

CUSTOM FABRICATION IN TWO WEEKS IN NEW JERSEY




Single Bullnose Coping Project



Double Bullnose Coping Project



Mitered steps and custom drains





MOON 20"X40"
IN STOCK





DRIVEWAYS



MOON & DESERT 20"X40"
IN STOCK





PIETRA ANTRAZYT 3 CM





THE STANDARD

TO DATE, THERE ARE NO STANDARDS RELATING TO RAISED OUTDOOR FLOORING.

THE ONLY STANDARD THAT CAN ACT AS A REFERENCE IS UNI EN 12825, WHICH SPECIFIES THE FEATURES AND PERFORMANCE REQUIREMENTS OF RAISED FLOORINGS MAINLY INTENDED TO BE USED INSIDE BUILDINGS.

PORCELAIN 2CM PAVER MEETS THE REQUIREMENTS OF THIS STANDARD (LISTED IN THE FOLLOWING TABLE).

WITH REGARD TO THE "DYNAMIC LOAD - SHOCK-PROOF TEST AGAINST HARD BODIES", WE RECOMMEND CHOOSING THE MATERIAL ACCORDING TO THE INTENDED USE AND USING STRUCTURES THAT ARE MAXIMUM 100 MM HIGH.

Type of tests	Test result
Static load - Load test on the element	Test passed
Vertical loading test on column	Test passed, as declared by the support supplier
Permanent deformation test on the element	Test passed
Dynamic load - Shock-proof against hard bodies	Test not passed
Dynamic load - Shock-proof against soft bodies	Test passed
Length of the panel sides	Test passed
Panel orthogonality	Test passed
Straightness of the sides	Test passed
Panel thickness	Test passed
Panel warpage	Test passed
Vertical bending of the panels	Test passed

FINE PORCELAIN STONEWARE

	Technical features	Reference standard or testing method	Value required according to standards	Assessed value
Dimensions and quality of the surface	Length and width (acceptable deviation (%) of the average size of each tile from the manufactured W size)	UNI EN ISO 10545-2	± 0,6 % (± 2,0 mm)	Compliant
	Thickness		± 5 % (± 0,5 mm)	
	Straightness of the edges		± 0,5 % (± 1,5 mm)	Compliant
	Orthogonality		± 0,5 % (± 2,0 mm)	Compliant
	Planarity		± 0,5 % (± 2,0 mm)	
	Surface quality		Minimum 95% of the tested tiles must be free from visible defects	Compliant
Physical properties	Mass of water absorbed	UNI EN ISO 10545-3	Eb ≤ 0,5 %	≤ 0,1 %
	Breaking strength (S) – Flexural resistance (R)	UNI EN ISO 10545-4	S > 1300 N R > 35 N/mm ²	> 10000 N > 45 N/mm ²
	Resistance to frost	UNI EN ISO 10545-12	Request	Compliant
	Deep abrasion resistance	UNI EN ISO 10545-6	≤ 175 mm ³	Compliant
	Resistance to thermal shocks	UNI EN ISO 10545-9	Available test method	Compliant
	Coefficient of linear thermal dilation	UNI EN ISO 10545-8	Available test method	Compliant
Chemical properties	Resistance to chemical products	UNI EN ISO 10545-13	They must not show relevant signs of chemical attacks	Compliant
	Stain resistance	UNI EN ISO 10545-14	Minimum class 3	Compliant
Safety	Coefficient of kinetic friction	ANSI A 137.1 - DCOF	Wet > 0.42	> 0,42
		B.C.R.A.	D.M. μ>0.4	>0.4
	Classification □□ non-slip	DIN 51130	Depending on the workplace or work area	R11
		DIN 51097	Depending on the wet areas subject to barefoot traffic	A+B+C

With the exception of special pieces and decors





PACKAGING DETAILS

PORCELAIN PAVERS PACKAGING INFORMATION						
Group Name	Product Name	Product Size	Quantity In Crate/sq ft	Quantity In Crate/pcs	Weight of Crate/lbs	Dimensions of Crate
20x40	Alpine, Dark, Desert, Dust, Moon, Sand, Silver, Smokey, Sunset, White, Pergamo, Efeso	20"x40"x3/4"	233.3 (new) 195 (old)	42 in new boxes 35 in old boxes (1 pc in a box)	2084 in new boxes	L42"xD42"xH26"
24x24	Rustic White Soft Cream Pietra Grey Rustic Grigio Forge Pocono	24"x24"x3/4"	240	60 (2 pcs in a box)	2.183	L47"xD32"xH30"
	Ash Coal Metal Sandstone	24"x24"x3/4"	240	60 (2 pcs in a box)	2.149	L47"xD31"xH29"
	Milk Caramel Storm Honey	24"x24"x3/4"	256	64 (2 pcs in a box)	2.822	L45"xD45"xH29"
	Light Grey Dark Grey	24"x24"x3/4"	256	64 (2 pcs in a box)	2.822	L45"xD45"xH29"
Wood Look	Carpino Rovere Impero Rovere Sabbia	8"x48"x3/4"	213	80 (2 pcs in a box)	2.602	L48"xD32"xH28"
		16"x48"x3/4"	256	48 (1 pc in a box)	2.084	L51"xD43"xH20"
Cement Look	Antracite Avorio Grigio	32"x32"x3/4"	284,5	40 (1 pc in a box)	2.566	L47"xD37"xH37"
Modular Pattern 4 Sizes	Ash Coal Metal Sandstone	12"x24"x3/4"	240	120 (3 pcs in a box)	2.167	L47"xD31"xH29"
		18"x18"x3/4"	243	108 (3 pcs in a box)	2.215	L47"xD39"xH23"
		18"x36"x3/4"	243	54 (2 pcs in a box)	2.200	L47"xD39"xH23"
		24"x24"x3/4"	240	60 (2 pcs in a box)	2.149	L47"xD31"xH29"
Antiqued Wave Edge	Quarzite Mix Belgisch Granit	16"x32"x3/4"	192	54 (2 pcs in a box)	1.711	L47"xD32"xH21"
Modular Pattern 3 Sizes	Light Grey Dark Grey Milk Caramel Storm Honey	12"x24"x3/4" 24"x24"x3/4" 24"x36"x3/4"	252	14 Sets	2.214	L48"xD38"xH32"
24"x48" & 24"x72"	Light Grey Dark Grey Slate Taupe Milk Caramel Storm Honey	24"x48"x3/4"	256	32 (1 pc in a box)	2.187	L48"xD26"xH24"
		24"x72"x3/4"	264	22 (1 pc in a box)	2.187	L72"xD26"xH24"
Driveway- Sidewalk	Oriente Quarzite	9"x9"x3/4"	248	440 (11 pcs in a box)	2.161	L48"xD32"xH20"
		9"x18"x3/4"	225	200 (5 pcs in a box)	1.982	L48"xD32"xH20"
48"x48"	Volcano Grey Aspen White Volcano Dark Corten Antique Sand Antique Grey Antique Earth	48"x48"x3/4"	320	20 (1 pc in a box)	2.760	L48"xD48"xH20"
Porcelain Veneer	Avorio Beige Brown Grigio	8"x24"x3/8"	579	448 (7 pcs in a box)	2.381	L47"xD32"xH30"
	Avorio Beige Brown Grigio	Corner 8"x24"x3/8"	sold by pcs	40 (7 pcs in a box)		
Porcelain Ledger	Taupe Beige White Grey Dark	6"x24"x3/8"	528	528 (11 pcs in a box)	1.958	L47"xD32"xH30"
		Corner 6"x(8"+4")x3/8"	sold by pcs	48 (6 pcs in a box)		
3cm	Bluestone Dark Bluestone Grey Pietra Barge	16"x32"x1 1/4"	192	54 (1 pc in a box)	2.656	L50"xD32"xH22"





Scan to visit our
YouTube channel

