

# TRACKED SLOPE MOWERS



DESIGNED + BUILT IN THE USA



## REMOTE-OPERATED SLOPE MOWERS THAT CREATE OPPORTUNITIES.

Heavy-duty slope mowers for maintaining steep slopes & hillsides up to 50 degrees.

### IDEAL FOR:

- Hillside & steep-incline maintenance
- Wetland & swamp preservation
- Dam & levy embankments
- Landfill slope preservation
- Retention or water treatment ponds
- Roadside mowing



**TK-60XP**



**TK-52XP**



**TK-44E**



# TRACKED SLOPE MOWER COMPARISON



DESIGNED + BUILT IN THE USA



## TK-60XP



## TK-52XP



## TK-44E

ENGINE	Kawasaki® FX1000 EFI	Kawasaki® FX850V	Kawasaki® FR651V
HORSEPOWER	38.5	27	21.5
DISPLACEMENT	999 cc	852 cc	726 cc
DRIVE SYSTEM	Hydro-Gear® ZT-5400 Transaxles	Hydro-Gear® ZT-5400 Transaxles	Hydro-Gear® ZT-3100 Transaxles
FUEL CAPACITY	13.4 Gallons	13.4 Gallons	5 Gallons
GROUND SPEED	6.7 mph (Transport) / 5.7 mph (Mowing)	6.7 mph (Transport) / 5.7 mph (Mowing)	4.5 mph (Transport) / 4.2 mph (Mowing)
CUTTING WIDTH	60 Inches	52 Inches	44 Inches
ACRES PER HOUR	3.1	2.7	1.7
SLOPE CLIMB ABILITY	50 Degrees	50 Degrees	45 Degrees
DECK CONSTRUCTION	Fabricated 7 Ga. Steel	Fabricated 7 Ga. Steel	Fabricated 10 Ga. Steel
DECK ENGAGEMENT	Ogura® Electric Clutch	Ogura® Electric Clutch	Ogura® Electric Clutch
CUTTING HEIGHTS	2.5 - 6.5 Inches	2.5 - 6.5 Inches	2.5 - 6.0 Inches
TRACK CONSTRUCTION	Rubber Molded Over Steel Links	Rubber Molded Over Steel Links	Rubber Molded Over Steel Links
TRACK SIZE / STYLE	9 Inches / Tread Style 'J'	9 Inches / Tread Style 'J'	7 Inches / Tread Style 'Wave'
WEIGHT	1,855 Pounds	1,790 Pounds	1,220 Pounds
LENGTH	87 Inches	86 Inches	82 Inches
WIDTH	86 Inches	78 Inches	63 Inches
HEIGHT	49.5 Inches	49.5 Inches	34 Inches
WARRANTY	2 Years / 400 Hours	2 Years / 400 Hours	1 Year / 200 Hours

Customer Support: 920-634-2227 • [www.rcmowersusa.com](http://www.rcmowersusa.com)