

GATOR NITRO JOINT SAND is the ideal air cure, permeable jointing material. It is a ready-to-use mixture of calibrated sand and proprietary resin formula which cures when exposed to air, hardening from top to bottom of the joint. The product can be installed in wet or dry weather.

IDEAL FOR

Residential and Commercial Pedestrian applications with:

- NEW Porcelain Tile with Gator Tile System Natural Stone
 - Natural StoneWetcast Stone
 - Concrete Pavers

FEATURES

- Permeable *
- Apply rain or shine
- Strength from top to bottom **
- 25% More strength
- 25% Faster setting time

GATOR NITRO JOINT SAND is recommended for a variety of uses, including patios, walkways, pool decks and driveways. The pavers, porcelain tiles, natural or wet cast stones must be installed on a drainage base system for pedestrian and light vehicular traffic applications and Gator Base systems for pavers, porcelain tiles, natural or wet cast stones for pedestrian applications only.

Note: Outdoor Porcelain tiles must be installed using Gator Tile System with minimum joint depth of 3/4".

JOINTS REQUIREMENTS AND APPLICATIONS

	Minimum joint width	Maximum joint width	Minimum joint depth	Pedestrian	Vehicular
Porcelain Tiles with Gator Tile System	1/8"	1/4"	3/4"	1	x
Stones	3/16"	2"	1"	1	х
Interlocking Concrete Pavers	3/16"	2"	2-3/8"	1	1

4 BEAUTIFUL COLORS









- * Permeable as installed. If not maintained, permeability will be obstructed over time.
- ** Gator Nitro Joint Sand will harden from top to bottom up to 2 3/8".

INSTALLATION STEPS

Designed for pedestrian applications and residential driveways, Gator Nitro Joint Sand is ready-to-use and does not require any mixing. Installation will be easier with two people.



Compact first, then wet the paved surface.



Spread, wet and fill joints with Gator Nitro Sand.



Remove all excess Gator Nitro Sand by rinsing and brushing until the entire paved surface is clean. Please read our TDS (visit AllianceGator.com) for the complete installation steps.



