

# LED MR-16 GUIDE

*Color-Coded & Engraved for Easy Identification*

## Applications

Shaded Lamp Code = Featured Applications



Uplighting 10-20ft. Trees  
**Green 40° Wide Lamp**


Uplighting 20-30ft. Trees  
**Blue 30° Medium Lamp**

Uplighting 30-40ft. Trees  
**Black 30° Medium Lamp**

Uplighting 40+ ft.  
**White 30° Medium Lamp**



Moon Lighting  
**Blue 55° X-Wide Lamp**



Wall Washing / 10 ft. or lower  
plant material /  
MR-16 Area Light  
**Red 80° XX-Wide Lamp**

Uplighting 30-40ft.  
Palm Tree  
**White 20° Narrow Lamp**


Uplighting Columns/  
Architecture  
**Green 20° Narrow Lamp**



Grazing/ Two Story House  
Facade  
**Blue 30° Medium Lamp**



Technique: Shadowing  
**Blue 40° Wide Lamp**



Flag Poles, Columns, Palm Trees	House Facade / Grazing	General Purpose Uplighting	Moonlighting / Wall Washing	Wide Wall Washing
<b>20° Narrow Beam Spread</b>	<b>30° Medium Beam Spread</b>	<b>40° Wide Beam Spread</b>	<b>55° X-Wide Beam Spread</b>	<b>80° XX-Wide Beam Spread</b>



## LED MR-16 LAMP GUIDE

NEW 3000K Color Temp Lamps

 <b>Lamp Code</b>	Beam from Fixture		Halogen Equiv.	Lamp Body Color Code	Voltage Input	Color Temp. CCT/CRI	Amps	Power Factor	Volt Amp (to size)	Factory Lumen	Lumen Output Enclosed Fixture	Rated Hrs.
SLMR166XXW27	XX-Wide	80°	75 Watt	WHITE 6 Watt	10-24 VAC	2700°K/ 83 CRI	0.706	0.717	8.49	720	213	50,000
SLMR166XW27	X-Wide	55°									440	
SLMR166W27	Wide	40°									527	
SLMR166M27	Medium	30°									575	
SLMR166N27	Narrow	20°									559	
SLMR166XW30	X-Wide	55°				534						
SLMR166W30	Wide	40°				557						
						3000°K/ 83 CRI	0.762	0.681	9.16			
SLMR165XXW27	XX-Wide	80°	50 Watt	BLACK 5 Watt	10-24 VAC	2700°K/ 83 CRI	0.542	0.7	6.56	540	175	50,000
SLMR165XW27	X-Wide	55°									392	
SLMR165W27	Wide	40°									419	
SLMR165M27	Medium	30°									421	
SLMR165N27	Narrow	20°									381	
SLMR165XW30	X-Wide	55°				426						
SLMR165W30	Wide	40°				456						
						3000°K/ 83 CRI	0.671	0.658	7.45			
SLMR164XXW27	XX-Wide	80°	35 Watt	BLUE 4 Watt	10-24 VAC	2700°K/ 83 CRI	0.387	0.691	4.67	390	199	50,000
SLMR164XW27	X-Wide	55°									299	
SLMR164W27	Wide	40°									304	
SLMR164M27	Medium	30°									305	
SLMR164N27	Narrow	20°									267	
SLMR164XW30	X-Wide	55°				310						
SLMR164W30	Wide	40°				322						
						3000°K/ 83 CRI	0.435	0.637	6.0			
SLMR162XXW27	XX-Wide	80°	20 Watt	GREEN 2 Watt	10-24 VAC	2700°K/ 83 CRI	0.236	0.664	2.83	300	128	50,000
SLMR162XW27	X-Wide	55°									183	
SLMR162W27	Wide	40°									189	
SLMR162M27	Medium	30°									193	
SLMR162N27	Narrow	20°									167	
SLMR162XW30	X-Wide	55°				197						
SLMR162W30	Wide	40°				196						
						3000°K/ 83 CRI	0.249	0.64	3.0			
SLMR161XXW27	XX-Wide	80°	10 Watt	RED 1 Watt	10-24 VAC	2700°K/ 83 CRI	0.139	0.63	1.69	240	74	50,000
SLMR161XW27	X-Wide	55°									106	
SLMR161W27	Wide	40°									104	