

Premier™ 8 Retaining Wall Block



Premier 8 is one of the most innovative SRW products the industry has seen in its 30 year history. Its unique and patented 1 sq. ft. block design is changing the industry. Premier's 54 lb. unit weight reduces installer fatigue and beats all other block systems for strength, performance, freight efficiencies and ease of construction.

www.rockwoodwalls.com



Appearance
Dependability
Efficiency

ROCKWOOD[®]
RETAINING WALLS
A better way.[™]

Premier™ 8 Retaining Wall Block



Pound for pound, Premier 8 is unlike any other SRW block.

Premier 8's revolutionary block design makes it the most efficient 1 sq. ft. SRW block ever. At just 54 lbs., it beats all other block systems for freight efficiencies and ease of construction.

Features and specifications:


- Easy to handle for increased efficiencies in the field
- No cumbersome/expensive pins or clips
- Capable of tight radius turns
- Allows for up to 864 sq. ft. per truckload

Dimensions: 18" W x 12" D x 8" H (457 x 305 x 203mm)
Weight: 54 lbs. (24.5 kg)
Area: 1.0 sq. ft.
Setback: 1.0" (7°)

Manufactured in accordance with ASTM C1372. Unit availability, color and specifications vary by manufacturer. Contact your nearest Rockwood manufacturer or dealer for more information.

Premier's straight-thru cores fill easily with drainage material that create "vertical stone columns" to increase grid connection strength and resistance to shear.

Premier 8's bottom side anchor bar creates an automatic 7° setback.



ROCKWOOD[®]
RETAINING WALLS
A better way.[™]

325 Alliance Place NE
Rochester, MN 55906

phone: (507) 529-2871
fax: (507) 529-2879
www.rockwoodwalls.com

Available at: